

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 853 205 B1

(12)

EUROPEAN PATENT SPECIFICATION

(45) Date of publication and mention
of the grant of the patent:
09.04.2003 Bulletin 2003/15

(51) Int Cl.7: **F16K 7/12**

(21) Application number: **97122430.8**

(22) Date of filing: **18.12.1997**

(54) **Improved spring diaphragm for shut-off valves and regulators**

Federmembran für Absperrventile und Regler

Membrane à ressort pour des soupapes d'arrêt et des régulateurs

(84) Designated Contracting States:
ES FR GR IT

(30) Priority: **05.01.1997 IL 11996397**

(43) Date of publication of application:
15.07.1998 Bulletin 1998/29

(73) Proprietor: **Raphael Valves Industries (1975) Ltd.**
Or Akiva 30600 (IL)

(72) Inventor: **Frenkel, Boris, Dr.**
Netanya 42320 (IL)

(74) Representative: **Modiano, Guido, Dr.-Ing. et al**
Modiano, Josif, Pisanty & Staub,
Baaderstrasse 3
80469 München (DE)

(56) References cited:
GB-A- 2 031 122 **US-A- 2 302 930**
US-A- 2 710 629 **US-A- 2 840 339**

EP 0 853 205 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid. (Art. 99(1) European Patent Convention).

Description

[0001] The present invention relates to diaphragm used in shut-off valves and regulators and more particularly to an improved spring diaphragm for shut-off valves and regulators for the hermetic separation of adjacent chambers of valves under pressure, as well as for the possibility of regulating the magnitude of the flow passing through a pipeline.

[0002] The spring diaphragm according to the invention is of unique construction, which will be referred to hereinafter as "two-storey diaphragm", can be employed in devices used in water-supply systems and in pipelines transporting petroleum, gas, various kinds of acids and bases, and other liquid mixtures and solutions.

[0003] A diaphragm which is intended for similar purposes and can be employed in similar devices is known (see "Fluid Controlling Diaphragm Valve," England, Classes: 135, F16k 7/16, No. 34131).

[0004] This diaphragm has the form a disk of molded shape made of rubber, at its center there is provided a bolt for joining the diaphragm to an actuator.

[0005] The outer shape of the diaphragm repeats the shape of the inner surface of the valve body, and the inner surface of the diaphragm corresponds to the outer surface of the actuator.

[0006] The top of the actuator is connected to a screw, which is screwed into a bushing, on which a handwheel is fixedly attached.

[0007] The ascent of the diaphragm into the upper position and its descent into its lower position are effected by rotating the handwheel in the clockwise and counter-clockwise directions.

[0008] Hermetic sealing of the valve (separation of the entrance and exit chambers) is effected by tightly compressing the diaphragm against the surface of the valve body with the aid of the actuator.

[0009] One deficiency of such diaphragm is the fact that it can be operated (the valve can be opened and closed) only by manual control and can be employed only in shut-off valves.

[0010] Such a diaphragm design cannot be employed in regulator valves, i.e., in devices which automatically regulate the value of the pressure or pressure drop.

[0011] Another shortcoming of the design of this diaphragm is the fact that its operation requires a manual drive mechanism that includes several parts (an actuator, a screw, a bushing, and a handwheel), which increases the weight of the valve and the amount of work going into its manufacture and reduces the lifetime of the valve and its reliability during service.

[0012] The diaphragm design described in U.S. Patent No. 2,302,930 which can be employed in similar devices for similar purposes, is also known. The design of this diaphragm is in the form of an elastic disk which transforms into a spherical surface. On the convex side of the spherical surface, which comes into contact with

the surface of the valve body, there are hermetically sealing bands arranged along the perimeter of the elastic disk, which are joined to one another by an hermetically sealing band located on the symmetry axis of the diaphragm.

[0013] This diaphragm provides for valve operation (opening and closing) using an hydraulic drive mechanism and a metallic restoring spring placed over the diaphragm. A valve with a diaphragm of such construction opens (the diaphragm rises into the upper position) when there is positive pressure below the diaphragm. The valve closes (the diaphragm drops into the lower position until contact is made with the valve body) either under the action of the restoring spring (in the absence of pressure in the pipeline system) or when a pressure is supplied to the chamber above the diaphragm. When the pressures above and below the diaphragm are equal, the latter descends under the action of the restoring force of the metallic spring.

[0014] One deficiency of this diaphragm is the fact that at low pressure drops and low flow rates the presence of the metallic spring creates vibrations, which rapidly destroy the diaphragm and render the valve ineffective.

[0015] Another deficiency of this design is the fact that the restoring force of the spring must be overcome to completely open the valve, and, as a result, there is an increase in the value of the minimal pressure needed to completely open the valve.

[0016] A third deficiency of this design is the presence of the spring and its seat, which complicates the design of the valve as a whole and its assembly and shortens the lifetime of both the diaphragm and the valve as a whole.

[0017] The diaphragm described in application No. 62466 (Improved Diaphragm for Valves, April 30, 1993) is also known. Its appearance resembles the diaphragm described in U.S. Patent No. 2,302,930; however, this diaphragm is distinguished by the presence of radial and annular ribs on its concave surface, which perform the role of a metallic spring and replace the latter.

[0018] This diaphragm eliminates all the deficiencies described above and has several significant advantages over them.

[0019] This diaphragm design is very efficient when it is employed in valves with through apertures of relatively small nominal diameters (from 1/2" to 8").

[0020] In valves with larger nominal apertures (more than 8") there is a sharp increase in the active area of the diaphragm, which, in turn, requires an increase in the geometric dimensions (width and height) of the ribs arranged on the concave surface of the diaphragm.

[0021] One deficiency of this technical solution is the need to increase the minimal pressure required to open the valve, i.e., the hydraulic characteristics of the valve become poorer.

[0022] It is thus the object of the present invention to provide a diaphragm for valves of large nominal aper-

tures which does not have said deficiency.

[0023] The object of the invention is achieved by constructing a diaphragm in the form of a flexible elastic disk consisting of two storeys connected to one another. The lower part, which performs the function of an hermetic seal that separates the inlet and outlet chambers of the valve, interacts with the inner surfaces of the valve body and the bonnet, and the upper part, which performs the function of a spring, interacts with the inner surface of the bonnet and the concave surface of the lower part of the disk.

[0024] In order to increase the lifetime, springy ribs which create the force and the unit pressure needed to ensure hermetic sealing between the diaphragm and the valve body are provided on the curvilinear concave surface of the lower part of the flexible elastic disk, and ribs which create only the force needed to return the diaphragm from the uppermost position (the state of an opened valve) to the lower position (the state of a closed valve) are arranged on the upper part of the flexible elastic disk.

[0025] The invention will now be described with reference to the annexed drawings in which:

Figure 1 shows the design of the diaphragm according to the invention in cross section.

Figure 2 is a top view of figure 1.

Figure 3 shows a variant of the design of the diaphragm, in which the flexible elastic disk is constructed of two separate parts, which are joined to one another by fastening elements.

Figure 4 is an underneath view of figure 3.

Figure 5 shows the diaphragm installed in an assembled shut-off valve in its lowermost position (the valve is closed).

Figure 6 shows the diaphragm in a position in which the upper part of the flexible elastic disk is in contact with the inner surface of the valve bonnet.

Figure 7 shows the diaphragm in the uppermost position (the valve is completely opened).

[0026] The diaphragm seen in Figure 1 consists of flexible elastic disk 1, which is constructed in the form of two parts joined to one another, i.e., lower part 2 and upper part 3.

[0027] Within the lower part there is a scarcely deformable, thin stiff elastic sheet 4, for example, of cotton or nylon, which imparts the necessary stiffness to the diaphragm operating under pressure.

[0028] On the convex surface of the lower part 2 there is provided a central hermetically sealing ridge 5, which is joined to annular hermetically sealing ridges 6, with

the aid of which hermetic sealing is ensured between the diaphragm and the valve body.

[0029] On both sides of the hermetically sealing ridge 5 there are provided ribs 7, which are intended for damping the noise and vibrations appearing during operation of the valve.

[0030] In the central part of the concave surface of the lower part 2 there is a solid disk 8, from which springy ribs 9 branch out in the radial direction at equal distances from one another.

[0031] The radically arranged, springy ribs 9 create the force and unit pressure needed to ensure hermetic sealing between the diaphragm and the inner surface of the valve body.

[0032] Beyond the radial ribs 9 there are annular hermetically sealing ridges 10, which serve to ensure hermetic sealing between the diaphragm and the valve bonnet.

[0033] The convex part of the upper part 3 is joined to the solid disk 8, which is located on the lower part of the flexible elastic disk.

[0034] In the central section of the concave surface of the upper part of the flexible elastic disk there is a ring 11, which is made as a single unit together with the concave surface of the upper part, from which springy ribs 12 branch out in the radial direction. The latter create only the force needed to return the diaphragm from the uppermost position to the lower position.

[0035] On the flat surface of the lower layer of the diaphragm there are provided holes 13, through which the bolts which fasten the bonnet and the diaphragm to the valve body pass.

[0036] Bearing areas 14 (Figure 5), which come into contact with ribs located in the valve body, are provided on the convex surface of the lower part on both sides of the hermetically sealing band perpendicularly to its axis.

[0037] The fundamental significant difference between the design of the proposed diaphragm and all the known valves is that the functions of the springy ribs are clearly demarcated in it. More specifically:

- the springy ribs located on the lower part create the force needed to ensure hermetic sealing of the valve;
- the springy ribs located on the upper part create the force needed to return the raised diaphragm to the lower position.

[0038] A positive effect greater than the sum of the component parts is achieved in such a design embodiment, since it creates the possibility for maintaining the minimal pressure needed to raise the diaphragm to the uppermost position and for maximally increasing the area of the aperture cross section without increasing its weight, while the lifetime of the diaphragm increases.

[0039] In order to simplify the manufacturing technology, the diaphragm can be constructed as separable components (Figure 3).

[0040] In this case the lower part 2 and the upper part 3 are made separately, and then joined to form a single unit with the aid of fastening elements; a screw bolt 15 and disk 16, To make such joining possible, metallic bushing 17, into which screw bolt 15 is screwed, is provided at the center of the lower part.

[0041] Such a sectional embodiment of a diaphragm consisting of two separate parts does not alter the essence of the invention and the operating principle of the diaphragm.

[0042] The diaphragm operates in the following manner (in the example case of a shut-off valve which performs an opening-closing function).

[0043] The two-storeys diaphragm 1 (Figure 5) is placed on flange 18 of the valve body and covered by bonnet 19 from above.

[0044] The diaphragm is tightly compressed between the bonnet and the valve body with the aid of bolt 20 to ensure hermetic sealing of the joint.

[0045] Three-way valve 21, with the aid of which the operation of the diaphragm is obtained, is placed on the bonnet.

[0046] The idea is that in the through aperture of the valve body there is constantly a pressure P_1 on the inlet side, and a pressure P_2 on the outlet side, and the diaphragm is in the lowermost position (the valve is closed).

[0047] In this case the handle of the three-way valve is placed in position A, in which the pressure P_1 is supplied through pipe 22 to the compartment over the diaphragm.

[0048] In this case the hermetically sealing ridge 5 is tightly pressed against bearing surface 23 in the valve body by the force created by the pressure P_3 and the force T_9 created by the springy ribs 9.

[0049] It is very important that at this moment the springy ribs 12 located on the upper part of the diaphragm do not participate in the process of hermetically sealing the valve, since it is in the free state, and this is necessary, since it is clear from the equality

$$P_1 \cdot F_1 / 2 < P_3 \cdot F_1 + T_9 \quad (1)$$

that P_1 acts on half of the active area of the diaphragm when the valve is closed.

[0050] If it is assumed that the effective areas of the diaphragm F_1 from above and below are equal, it follows from inequality (1) that the total force stemming from the action of the pressure P_3 on the area F_1 ($P_3 \cdot F_1$) and from the action of the springy ribs 9 (T_9) is significantly greater than the force acting on the diaphragm from below ($P_1 \cdot F/2$), owing to which separation of the inlet and outlet compartments in the valve occurs, i.e., in this situation the valve is always closed, since the hermetically sealing ridge 5 is tightly pressed against the bearing surface 23 in the valve body in this situation.

[0051] In the case in which the pressure $P_3 = P_1$ acts

on the diaphragm from above, the pressure at the exit is $P_2 = 0$, and the diaphragm tends to turn into a position in which part of the area on the outlet side is lower than the part of the area on the inlet side.

[0052] In order to eliminate the possibility of such fuming, bearing areas 14 were provided on the diaphragm (Figure 4). When the diaphragm descends, they lie on rib bearing surface 24 in the valve body (Figure 5).

[0053] In addition, the bearing areas 14 increase the cross section of the diaphragm and imparts greater strength to it in these places.

[0054] In order to open the valve, the handle of the three-way valve 21 must be turned to position B (this is illustrated by the dotted line in Figure 5).

[0055] In this position the flow from the inlet side (the pressure P_1) is blocked (the pressure P_1 does not reach the chamber over the diaphragm), and the chamber over the diaphragm is open to the atmosphere, i.e., $P_3 = 0$.

[0056] Under the action of the pressure P_1 a force appears on half of the area of the convex part of the diaphragm ($P_1 \cdot F_2$) which begins to move the diaphragm upward until the through aperture of the valve is opened completely.

[0057] When the diaphragm rises, the springy ribs 9 stretch, and tensile stresses appear in them, which tend to return the diaphragm to its original (lower) position, but this force need not provide for the return of diaphragm to the lower position, since according to the scheme of the design proposed in the present application (and this is the main point of the invention), this force should basically ensure only hermetic sealing of the valve in the closed position.

[0058] As soon as the diaphragm rises to the position in which the upper part touches the inner surface of the bonnet, the springy ribs 12 go into operation (see Figure 6).

[0059] When the diaphragm rises further (Figure 7), the springy ribs 12 begin to stretch, and tensile stresses appear in them, which also create the main force that returns the diaphragm to its initial position. The springy ribs 9 also create an additional force, which tends to return the diaphragm to its initial position.

[0060] To close the valve (to lower the diaphragm) the handle of the three-way valve 21 must be moved into position A, in which the pressure P_1 is supplied to the chamber over the diaphragm, and the channel connecting this chamber with the atmosphere is blocked.

[0061] The relation between the forces acting in this situation is expressed by the following inequality:

$$P_3 \cdot F + T_9 + T_{12} > (P_1 + P_2) F \quad (2)$$

[0062] Since $P_3 = P_1$ and $P_1 \geq P_2$, it is clear from inequality (2) that the force acting on the diaphragm from above will always be greater than the force acting on the

diaphragm from below.

[0063] The force T_{12} created by the springy ribs 12 will continue to act as long as they are in contact with the inner surface of the bonnet.

[0064] When the diaphragm descends further, the springy ribs 12 on the upper layer cease to make contact with the inner surface of the bonnet, $T_{12} = 0$, and the further descent of the diaphragm to its initial position takes place under the action of the force created by the pressure P_3 and the force of the springy ribs 9.

[0065] It is seen from the description that as the diaphragm rises to the uppermost position, the forces created by the springy ribs of both parts are summed at a definite moment and that as the diaphragm descends to the lowermost position, the force created by the springy rings 12 of the upper part becomes equal to zero at a definite moment.

[0066] Such embodiment makes it possible to maintain the minimal pressure needed to open the valve and, at the same time, to create the force needed to return the diaphragm to the lowermost position.

[0067] A valve design with a minimal pressure for opening the valve and a maximal aperture cross-sectional area without an increase in weight can be developed by varying the geometric dimensions of the surface of the upper part and the springy ribs located on it while leaving the geometric dimensions of the lower part of the diaphragm unchanged.

[0068] At the same, the lifetime of the diaphragm increases, since, first, the forces created by the springy ribs of the upper and lower parts of the diaphragm are demarcated and, second, there is a possibility for replacing only one part of the diaphragm (upper or lower) in the case of a separable sectional design.

[0069] Where technical features mentioned in any claim are followed by reference signs, those reference signs have been included for the sole purpose of increasing the intelligibility of the claims and accordingly, such reference signs do not have any limiting effect on the scope of each element identified by way of example by such reference signs.

Claims

1. A spring diaphragm for shut-off valves and regulators which comprises a first lower Part (2) in the form of a flexible elastic disc which performs the function of a hermetic seal separating the inlet and outlet chambers of the valve and a second upper part (3) of smaller size which performs the function of a spring, said second upper part (3) being integral with said first part or connected to said first part.
2. A spring diaphragm for shut-off valves and regulators as claimed in Claim 1 constructed in the form of a flexible elastic disk which smoothly transforms into a spherical surface; within the flexible elastic

disk there is a stiff, scarcely deformable, thin elastic sheet (4), for example, of cotton, nylon or another stiff, scarcely deformable material.

3. A spring diaphragm for shut-off valves and regulators as claimed in Claim 1 where on the surface of the flexible elastic disk there are hermetically sealing ridges (5, 6), which are made as a single unit together with the long curvilinear surface.
4. A spring diaphragm for shut-off valves and regulators, as claimed in Claim 1, **characterised by** springy ribs (9) which create the force and unit pressure needed to ensure hermetic sealing between the diaphragm and the valve body are provided on the concave surface of the lower part (2) of the flexible elastic disk, and ribs (12) which create only the force needed to return the diaphragm from the upper position (the state of an opened valve) to the lower position (the state of a closed valve) are arranged on the upper part (3) of the flexible elastic disk.
5. A spring diaphragm for shut-off valves and regulators, as claimed in Claim 1, **characterised in that** the upper part (3) of the flexible elastic disk is constructed in such a manner that the force needed to return the diaphragm to the lower position appears only at the moment when the upper part interacts (comes into contact) with the inner surface of the valve bonnet.
6. A spring diaphragm for shut-off valves and regulators; as claimed in Claims 1 to 5 **characterised by** the upper and lower parts can be constructed either as a single unit or as separate parts joined to one another by fastening elements (15, 16, 17).
7. A spring diaphragm for shut-off valves and regulators, as claimed in Claims 1 to 5 **characterised by** providing springy ribs (9, 12) on the lower and upper parts of the flexible elastic disk to create a uniformly distributed force over the entire active surface of the diaphragm.
8. A spring diaphragm for shut-off valves and regulators, as claimed in Claims 1 to 5 **characterised by** bearing areas (14) fashioned on the convex surface of the lower layer (2), which interact with bearing ribs in the valve body at the moment when the valve is closed, and there is a pressure in the chamber over the diaphragm.

Patentansprüche

1. Eine Federmembran für Absperrventile und Regler, die einen ersten untern Teil (2) in Form einer flexi-

blen elastischen Scheibe umfasst, der die Funktion einer hermetischen Dichtung erfüllt, die die Einlass- und Auslasskammern des Ventils trennt, und einen zweiten oberen Teil (3) einer kleineren Größe umfasst, der die Funktion einer Feder erfüllt, wobei der zweite obere Teil (3) mit dem ersten Teil integral ist oder mit dem ersten Teil verbunden ist.

2. Eine Federmembran für Absperrventile und Regler gemäß Anspruch 1, die in Form einer flexiblen elastischen Scheibe aufgebaut ist, die sanft in eine kugelförmige Oberfläche übergeht; innerhalb der flexiblen elastischen Scheibe ist eine starre kaum zu verformbare dünne elastische Folie (4), zum Beispiel aus Baumwolle, Nylon oder aus einem anderen starren kaum verformbaren Material.

3. Eine Federmembran für Absperrventile und Regler gemäß Anspruch 1, worin auf der Oberfläche der flexiblen elastischen Scheibe hermetisch abdichtende Wulste (5, 6) befindlich sind, die als eine einzige Einheit zusammen mit einer langen krummlinigen Oberfläche hergestellt sind.

4. Eine Federmembran für Absperrventile und Regler gemäß Anspruch 1, **gekennzeichnet durch** federnde Rippen (9), die die Kraft und den Einheitsdruck erzeugen, die erforderlich sind, um eine hermetische Dichtung zwischen der Membran und dem Ventilkörper zu sichern, die auf der konkaven Oberfläche des unteren Teils (2) der flexiblen elastischen Scheibe bereitgestellt sind, und **durch** Rippen (12), die nur die Kraft erzeugen, die erforderlich ist, um die Membran von der oberen Stellung (der Zustand eines geöffneten Ventils) zur unteren Stellung (der Zustand eines geschlossenen Ventils) zurückzuführen, die auf dem oberen Teil (3) der flexiblen elastischen Scheibe angeordnet sind.

5. Eine Federmembran für Absperrventile und Regler gemäß Anspruch 1, **dadurch gekennzeichnet, dass** der obere Teil (3) der flexiblen elastischen Scheibe derart aufgebaut ist, dass die Kraft, die erforderlich ist, um die Membran in die untere Stellung zurückzuführen, nur in dem Augenblick erscheint, wenn der obere Teil mit der inneren Oberfläche der Ventilkappe zusammenwirkt (in Kontakt kommt).

6. Eine Federmembran für Absperrventile und Regler gemäß den Ansprüchen 1 bis 5, **dadurch gekennzeichnet dass**, die oberen und unteren Teile entweder als eine einzige Einheit oder als getrennte Teile aufgebaut werden können, die miteinander durch Befestigungselemente (15, 16, 17) verbunden sind.

7. Eine Federmembran für Absperrventile und Regler gemäß den Ansprüchen 1 bis 5, **gekennzeichnet**

durch fehlende Rippen (9, 12) an den unteren und oberen Teilen der flexiblen elastischen Scheibe, um eine gleichmäßig verteilte Kraft über die gesamte aktive Oberfläche der Membran zu erzeugen.

8. Eine Federmembran für Absperrventile und Regler gemäß den Ansprüchen 1 bis 5, **gekennzeichnet durch** Trageabschnitte (14), die auf der konvexen Oberfläche der unteren Schicht (2) geformt sind, die mit tragenden Rippen im Ventilkörper zu dem Zeitpunkt zusammenwirken, zu dem das Ventil geschlossen ist und Druck in der Kammer über der Membran vorhanden ist.

Revendications

1. Membrane à ressort pour des soupapes d'arrêt et des régulateurs comprenant une première partie inférieure (2) se présentant sous la forme d'un disque élastique flexible, assurant la fonction de joint d'étanchéité hermétique séparant les chambres d'entrée et de sortie de la soupape, et une deuxième partie supérieure (3) de plus petite taille qui assure la fonction de ressort, ladite deuxième partie supérieure (3) étant réalisée d'une seule pièce avec ladite première partie ou étant reliée à ladite première partie.

2. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon la revendication 1, construite à la forme d'un disque élastique flexible qui se transforme progressivement en une surface sphérique; à l'intérieur du disque élastique flexible étant prévue une feuille élastique (4) mince, à peine déformable, rigide, par exemple en coton ou nylon, ou en un autre matériau à peine déformable, rigide.

3. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon la revendication 1, dans laquelle, sur la surface du disque élastique flexible sont prévues des filets (5, 6) assurant une fermeture hermétique, réalisées d'une seule pièce avec la surface curviligne longue.

4. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon la revendication 1, **caractérisée par** des nervures (9) élastiques, créant la force et la pression unitaire nécessaire pour assurer une fermeture hermétique entre la membrane et le corps de soupape, sont prévus sur les surfaces concaves de la partie inférieure (2) du disque élastique flexible, et des nervures (12), qui créent uniquement la force nécessaire pour le rappel de la membrane de la position supérieure (l'état d'une soupape ouverte) à la position inférieure (l'état d'une soupape fermée), sont agencées sur la partie supérieure (3) du disque élastique flexible.



5. Membrane. à ressort pour des soupapes d'arrêt et des régulateurs selon la revendication 1, **caractérisée en ce que** la partie supérieure (3) du disque élastique flexible est construite de manière que la force nécessaire pour rappeler la membrane à la position inférieure ne se manifeste qu'au moment auquel la partie supérieure interagit (vient en contact) avec la surface inférieure du capuchon de soupape. 5
- 10
6. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon les revendications 1 à 5, **caractérisée en ce que** les parties supérieure et inférieure peuvent être réalisées soit d'une seule pièce, soit sous forme de pièces séparées reliées les unes aux autres par des éléments de fixation (15, 16, 17). 15
7. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon les revendications 1 à 5, **caractérisée par** le fait de fournir des nervures (9, 12) élastiques sur les parties inférieure et supérieure du disque élastique flexible pour créer une force, répartie uniformément, sur la totalité de la surface active de la membrane. 20 25
8. Membrane à ressort pour des soupapes d'arrêt et des régulateurs selon les revendications 1 à 5, **caractérisée par** des surfaces de portée (14) façonnées sur la surface convexe de la couche inférieure (2), interagissant avec des nervures de portée prévues dans le corps de soupape, au moment auquel la soupape est fermée, et une pression régnant dans la chambre située au-dessus du diaphragme. 30 35



40



45

50

55










FIG. 7